



MATERIAL SAFETY DATA SHEET

LXLAB

Page: 1
1/24/2007

PARISER INDUSTRIES

PRODUCT NAME: LXLAB
TRADE SECRET REGISTRY #307554-5004P
UN NUMBER : N/A

HMIS CODES: H F R P
2 0 0 E

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PARISER INDUSTRIES
ADDRESS : 91 MICHIGAN AVE
PATERSON, NJ 07503

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 1/24/2007
INFORMATION PHONE : 973-569-9090 NAME OF PREPARER : ENVIRONMENTAL DEPT

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @ TEMP		PERCENT
SODIUM METASILICATE ANHYDROUS NOT ESTABLISHED	6834-92-0	N/A	N/A	44.56
SODIUM HYDROXIDE PEL=2mg/m3, CEILING TLV=2MG/M3, CEILING	1310-73-2	42mmHG	1000°C	11.88
ODORLESS MINERAL SPIRITS OSHA/PEL 300PPM TOTAL	64742-48-9	1	68°F	.49

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

pH 1% SOLUTION : 12.0 +/- .7
BOILING RANGE: 354°F - 1388°C
VAPOR DENSITY: N/A
COATING V.O.C.: NOT APPLICABLE
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: LIGHT TAN POWDER

SPECIFIC GRAVITY (H2O=1): 1.77
EVAPORATION RATE: N/A
MATERIAL V.O.C.: NOT APPLICABLE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : N/A METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.3 UPPER: 9.8

EXTINGUISHING MEDIA:
USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.



MATERIAL SAFETY DATA SHEET

LXLAB

Page: 2
1/24/2007

PARISER INDUSTRIES

SPECIAL FIREFIGHTING PROCEDURES

WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS WHEN EITHER IN CONFINED AREAS OR EXPOSED TO COMBUSTION PRODUCTS.
WEAR FULL PROTECTIVE CLOTHING.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DO NOT USE WATER TO FIGHT FIRE SINCE IN THE PRESENCE OF WATER, PRODUCT WILL REACT WITH SOME METALS TO LIBERAL HYDROGEN,
A FLAMABLE GAS.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID
NONE

INCOMPATIBILITY (MATERIALS TO AVOID)
ACIDS, METALS AND WATER

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
IN AQUEOUS SOLUTIONS, THIS MATERIAL MAY REACT WITH ALUMINUM, GALVANIZED IRON AND ZINC AND MAY GENERATE FLAMMABLE
HYDROGEN GAS AS A RESULT OF THIS REACTION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE IRRITATION OF THE NOSE AND THROAT. HIGH CONCENTRATION MAY CAUSE COUGHING AND CHOKING.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SKIN: THIS PRODUCT IS DESTRUCTIVE TO TISSUES CONTACTED AND PRODUCES SEVERE BURNS. A LATENT PERIOD MAY EXIST BETWEEN
EXPOSURE AND SENSE OF IRRITATION. EYE CONTACT: THIS PRODUCT IS DESTRUCTIVE TO EYE TISSUES ON CONTACT. WILL CAUSE
SEVERE BURNS THAT RESULT IN DAMAGE TO THE EYES AND EVEN BLINDNESS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SEE ABOVE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
THIS PRODUCT, IF SWALLOWED, CAN CAUSE SEVERE BURNS AND COMPLETE TISSUE PERFORATION OF MUCOUS MEMBRANES OF THE MOUTH,
THROAT, ESOPHAGUS, AND STOMACH.

HEALTH HAZARDS (ACUTE AND CHRONIC)
SEE ABOVE

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:



PARISER INDUSTRIES

MATERIAL SAFETY DATA SHEET

LXLAB

Page: 3
1/24/2007

No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
MAY AGGRAVATE EXISTING SKIN AND/OR EYE CONDITIONS ON CONTACT.

EMERGENCY AND FIRST AID PROCEDURES

EYES: OBJECT IS TO FLUSH MATERIAL OUT IMMEDIATELY THEN SEEK MEDICAL ATTENTION. IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST SEVERAL MINUTES HOLDING LIDS APART TO ENSURE FLUSHING OF THE ENTIRE SURFACE. WASHING EYES WITHIN 1 MINUTE IS ESSENTIAL TO ACHIEVE MAXIMUM EFFECTIVENESS. SEEK MEDICAL ATTENTION IMMEDIATELY. **SKIN:** WASH WITH PLENTY OF WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND FOOTWEAR. WASH CLOTHING BEFORE REUSE. FOOTWEAR SHOULD BE DECONTAMINATED BEFORE REUSE. SEEK MEDICAL ATTENTION IF SYMPTOMS ARE PRESENT. **INHALATION:** GET PERSON OUT OF CONTAMINATED AREA TO FRESH AIR. IF RESPIRATION STOPS, GIVE MOUTH-TO-MOUTH RESUSCITATION. SEEK MEDICAL ATTENTION IF SYMPTOMS ARE PRESENT. **INGESTION:** NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF SWALLOWED, DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER. (IF AVAILABLE, GIVE SEVERAL GLASSES OF MILK). IF VOMITING OCCURS SPONTANEOUSLY, KEEP AIRWAY CLEAR. SEEK MEDICAL ATTENTION IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

LEAKS SHOULD BE STOPPED. SPILLS SHOULD BE CONTAINED AND CLEANED UP IMMEDIATELY. SPILLS SHOULD BE REMOVED BY USING A VACUUM TRUCK. NEUTRALIZE REMAINING TRACES OF MATERIAL WITH ANY DILUTE INORGANIC ACID SUCH AS HYDROCHLORIC, SULFURIC, NITRIC, PHOSPHORIC, AND ACETIC ACID. THE SPILL AREA SHOULD THEN BE FLUSHED WITH WATER FOLLOWED BY LIBERAL COVERING OF SODIUM BICARBONATE. ALL CLEAN-UP MATERIAL SHOULD BE REMOVED AND PLACED IN APPROVED CONTAINERS, LABELED AND STORED IN A SAFE PLACE TO AWAIT PROPER TREATMENT OR DISPOSAL. SPILLS ON AREAS OTHER THAN PAVEMENT, I.E., DIRT OR SAND, MAY BE HANDLED BY REMOVING THE AFFECTED SOILS AND PLACING IN APPROVED CONTAINERS. PERSONS PERFORMING CLEAN-UP WORK SHOULD WEAR ADEQUATE PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING. SPILLS OR RELEASES SHOULD BE REPORTED, IF REQUIRED, TO THE APPROPRIATE LOCAL, STATE AND FEDERAL REGULATORY AGENCIES.

WASTE DISPOSAL METHOD

IF MATERIAL CANNOT BE SALVAGED, THE PREFERRED METHOD OF DISPOSAL IS IN A SECURE CHEMICAL LANDFILL IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT HANDLE UNLESS THE SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. AVOID EYE AND SKIN CONTACT. AVOID INHALATION OF DUST OR VAPORS. DO NOT PUNCTURE, DRAG OR SLIDE CONTAINERS. DO NOT SMOKE IN ANY CHEMICAL HANDLING OR STORAGE AREA. WASH HANDS BEFORE EATING.
STORE IN A COOL, DRY AND WELL-VENTILATED LOCATION. PROTECT FROM HUMIDITY. KEEP CONTAINERS TIGHTLY CLOSED. STORE AWAY FROM INCOMPATIBLE MATERIALS.

OTHER PRECAUTIONS

USE WITH ADEQUATE VENTILATION OR LOCAL EXHAUST. STORE IN A COOL, DRY WELL VENTILATED AREA. KEEP CONTAINER CLOSED WHEN NOT IN USE.

SECTION VIII - CONTROL MEASURES



PARISER INDUSTRIES

LXLAB

MATERIAL SAFETY DATA SHEET

Page: 4
1/24/2007

RESPIRATORY PROTECTION

NIOSH/MSHA APPROVED RESPIRATOR FOR PARTICULATES. LOCAL EXHAUST, VENTILATE AS REQUIRED.

VENTILATION

GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF.

PROTECTIVE GLOVES

CHEMICAL RESISTANT GLOVES SHOULD BE WORN. GLOVES MAY BE DECONTAMINATED BY WASHING WITH MILD SOAP AND WATER. NATURAL AND BUTYL RUBBER HAVE BEEN SUGGESTED.

EYE PROTECTION

DUST PROOF GLASSES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

PROTECTIVE CLOTHING MAY BE WORN, BUT IS GENERALLY NOT REQUIRED.

WORK/HYGIENIC PRACTICES

WARM WATER SHOWERING AND HANDWASHING IS SUGGESTED AFTER WORKING IN EXTREMELY DUSTY AREAS. EYEWASH STATIONS ARE RECOMMENDED IN THE WORK AREA. THOROUGHLY WASH WITH SOAP AND WATER BEFORE HANDLING FOOD, SMOKING OR APPLYING MAKEUP. WASH CONTAMINATED CLOTHING AND DRY BEFORE REUSE.

SECTION IX - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY PARISER INDUSTRIES, INC., TO BE ACCURATE. AS WITH ALL CHEMICALS, KEEP AWAY FROM CHILDREN, ANIMALS, AND FOOD PRODUCTS. FOR INDUSTRIAL USE ONLY, USE AS DIRECTED.

SECTION X - UN CODE

N/A