

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List) INKEX/INKOFF

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

PF 3017

Section I

Manufacturer's Name <u>EATON LABORATORIES INC.</u>	Emergency Telephone Number <u>(419)626-3967</u>
Address (Number, Street, City, State, and ZIP Code) <u>DIV. OF D.C. FILTER & CHEMICAL</u>	Telephone Number for Information <u>(419)626-3967</u>
<u>1517 FIFTH STREET</u>	Date Prepared
<u>SANDUSKY, OH 44870</u>	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	4b (optional)
<u>SEE PAGE II FOR HAZARDOUS COMPONENT LISTING.</u>				

THIS PRODUCT IS AN IRRITANT, FLAMMABLE, AND TOXIC.

THIS PRODUCT CONTAINS A REPORTABLE CHEMICAL UNDER SARA SECTION 302, 311, and/or 313.
THE COMPONENTS ARE AMYL ACETATE, XYLENE, METHANOL, AND METHYLENE CHLORIDE.

Section III — Physical/Chemical Characteristics

Boiling Point <u>INITIAL APPROX. 104°F</u>	Specific Gravity (H ₂ O = 1)	<u>0.86</u>
Vapor Pressure (mm Hg.) <u>ND</u>	Melting Point	<u>NA</u>
Vapor Density (AIR = 1) <u>ND</u>	Evaporation Rate (Butyl Acetate = 1)	<u>ND</u>

Solubility in Water EMULSIFIES

Appearance and Odor CLEAR, WATER-WHITE LIQUID WITH HIGHLY AROMATIC ODOR.

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) <u>CLOSED CUP 80°F</u>	Flammable Limits	LEL <u>.7%</u>	UEL <u>37.0%</u>
--	------------------	----------------	------------------

Extinguishing Media CARBON DIOXIDE, DRY CHEMICAL, FOAM, FOG

Special Fire Fighting Procedures USE SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER-PRODUCT MAY BURN WITH AN INVISIBLE FLAME

Unusual Fire and Explosion Hazards TOXIC FUMES EVOLVED FROM BURNING-KEEP AWAY FROM ALL SOURCES OF IGNITION, OPEN FLAME & SPARKS. DOT CLASSIFICATION: 1 FLAMMABLE LIQUID

(Reproduce locally) NA: NOT AVAILABLE ND: NOT DETERMINED OSHA 174, Sept. 1985

COMPONENTS	CAS#	OSHA	ACGIH TLV	%
MIBK Methyl Isobutyl Ketone	75-97-8	TWA 50ppm 205 mg/m ³ STEL 75ppm	STEL 100ppm TWA 50ppm 300mg/m ³	15.0%
XYLENE	1330-20-7	100ppm TWA 100ppm TWA	100ppm TLV/STEL	25.0%
METHANOL	67-56-1	200ppm TWA 200ppm TWA 260 mg/m ³	SKIN	25.0%
AMYL ACETATE	628-63-7	TLV-TWA 670mg/m ³ 125ppm	STEL 800mg/m ³ 150ppm	-----
METHYLENE CHLORIDE	75-09-02	500ppm(8hr) 100ppm CEILING VALUE	100ppm(8hr) TWA	10.0%
ODORLESS MINERAL SPIRITS	64741-65-7	400ppm(8hr day)		-----
SURFACTANTS	9016-45-9	NO LIMITS ESTABLISHED		-----

METHYLENE CHLORIDE

Methylene Chloride has been shown to increase the rate of spontaneously occurring malignant tumors in one strain of laboratory rats. Other animal studies, as well as several human epidemiology studies, failed to show a tumorigenic response relatable to Methylene Chloride is not believed to pose a measurable carcinogenic risk to man when handled as recommended. Birth defects are unlikely. Exposures having no effect on the mother should have no effect on the fetus. Did not cause birth defects in animals; other effects were seen in the fetus only at doses which caused toxic effects to mother. In animal studies has been shown not to interfere with reproduction. Negative or equivocal results have been obtained using mammalian cells or animals.

METHANOL

WARNING: Product contains Methanol. Ingestion of Methanol can cause serious harm. Ingestion even in small amounts can cause blindness or death, onset of symptoms can be delayed. See doctor immediately. May be absorbed through skin, WEAR GLOVES.