



1. MATERIAL AND COMPANY IDENTIFICATION

**Material Name** : ShellSol D40  
**Uses** : Industrial Solvent.  
**Product Code** : Q3362  
**Company** : Shell Chemical LP  
 PO Box 2463  
 HOUSTON TX 77252-2463  
 USA  
**MSDS Request** : 1-800-240-6737  
**Customer Service** : 1-866-897-4355

**Emergency Telephone Number**  
**Chemtrec Domestic (24 hr)** : 1-800-424-9300  
**Chemtrec International (24 hr)** : 1-703-527-3887

**Other Information** : ShellSol is a registered trademark of Shell trademark Management BV.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration
Solvent Naphtha (Petroleum), Medium Aliphatic	64742-88-7	100.00 %

3. HAZARDS IDENTIFICATION

Emergency Overview	
<b>Appearance and Odour</b>	: Light coloured. Liquid. Hydrocarbon.
<b>Health Hazards</b>	: Vapours may cause drowsiness and dizziness. Harmful: may cause lung damage if swallowed.
<b>Safety Hazards</b>	: Combustible liquid. Vapours are heavier than air. Vapours may travel across the ground and reach remote ignition sources causing a flashback fire danger.

**Health Hazards**  
**Inhalation** : Vapours may cause drowsiness and dizziness. Slightly irritating to respiratory system.  
**Skin Contact** : May cause moderate irritation to skin. Repeated exposure may cause skin dryness or cracking.  
**Eye Contact** : Vapours may be irritating to the eye.  
**Ingestion** : Harmful: may cause lung damage if swallowed.  
**Other Information** :  
**Signs and Symptoms** : Intentional abuse or misuse may cause organ damage or death. Respiratory irritation signs and symptoms may include a



temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. Heart damage may be evidenced by shortness of breath and, in severe cases, by collapse (cardiac arrest).

**Aggravated Medical Condition** : Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin. Respiratory system. Heart.

**4. FIRST AID MEASURES**

- Inhalation** : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- Skin Contact** : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
- Eye Contact** : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- Ingestion** : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (37° C), shortness of breath, chest congestion or continued coughing or wheezing.
- Advice to Physician** : Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Call a doctor or poison control center for guidance. Potential for cardiac sensitisation, particularly in abuse situations. Hypoxia or negative inotropes may enhance these effects. Consider: oxygen therapy.

**5. FIRE FIGHTING MEASURES**

Clear fire area of all non-emergency personnel.

- Flash point** : Typical 40 - 46 °C / 104 - 115 °F
- Explosion / Flammability limits in air** : 0.6 - 6 %(V)
- Auto ignition temperature** : 230 - 270 °C / 446 - 518 °F (ASTM E-659)
- Specific Hazards** : Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible.



Material Safety Data Sheet

- Extinguishing Media** : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment.
- Unsuitable Extinguishing Media** : Do not use water in a jet.
- Protective Equipment for Firefighters** : Wear full protective clothing and self-contained breathing apparatus.
- Additional Advice** : Keep adjacent containers cool by spraying with water.

---

6. ACCIDENTAL RELEASE MEASURES

Observe all relevant local and international regulations.

- Protective measures** : Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Material Safety Data Sheet. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.
- Clean Up Methods** : For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- Additional Advice** : See Chapter 13 for information on disposal. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Vapour may form an explosive mixture with air. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Centre at (800) 424-8802. Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Centre at (800) 424-8802. This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under



CERCLA.

7. HANDLING AND STORAGE

- General Precautions** : Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Handling** : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Avoid contact with skin, eyes, and clothing. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<= 1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Storage** : Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Storage Temperature: Ambient.
- Product Transfer** : Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling.
- Recommended Materials** : For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.
- Unsuitable Materials** : Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container Advice** : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Additional Information** : Ensure that all local regulations regarding handling and storage facilities are followed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

In the absence of occupational exposure standards for this product, it is recommended that the following are adopted.

Material	Source	Type	ppm	mg/m3	Notation
Stoddard Solvent	ACGIH	TWA	100 ppm		
	OSHA Z1	PEL	500 ppm	2,900 mg/m3	
	OSHA Z1A	TWA	100 ppm	525 mg/m3	



- Additional Information** : Shell has adopted as Interim Standards the OSHA Z1A values that were established in 1989 and later rescinded. Wash hands before eating, drinking, smoking and using the toilet.
- Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.
- Personal Protective Equipment** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN141. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.
- Hand Protection** : Longer term protection: Nitrile rubber gloves  
Incidental contact/Splash protection: PVC or neoprene rubber gloves  
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Eye Protection** : Chemical splash goggles (chemical monogoggles).
- Protective Clothing** : Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended air monitoring methods are given below or contact supplier. Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods, <http://www.cdc.gov/niosh/nmam/nmammenu.html>. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods, <http://www.osha-slc.gov/dts/sltc/methods/toc.html>. Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances, <http://www.hsl.gov.uk/search.htm>.
- Environmental Exposure Controls** : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Light coloured. Liquid.
Odour	: Hydrocarbon.
Boiling point	: Typical 149 - 213 °C / 300 - 415 °F
Flash point	: Typical 40 - 46 °C / 104 - 115 °F
Explosion / Flammability limits in air	: 0.6 - 6 %(V)
Auto-ignition temperature	: 230 - 270 °C / 446 - 518 °F (ASTM E-659)
Vapour pressure	: 300 Pa at 20 °C / 68 °F
Specific gravity	: 0.77 - 0.79 at 15 °C / 59 °F
Water solubility	: Insoluble.
Solubility in other solvents	: Hydrocarbon solvent(s) Soluble.
Vapour density (air=1)	: 4.8
Saturated Vapour concentration (in air)	: 18 g/m3 (estimated value(s))
Volatile organic carbon content	: 100 %
Molecular weight	: 143 g/mol

---

**10. STABILITY AND REACTIVITY**

<b>Stability</b>	: Stable under normal conditions of use.
<b>Conditions to Avoid</b>	: Avoid heat, sparks, open flames and other ignition sources.
<b>Materials to Avoid</b>	: Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

**11. TOXICOLOGICAL INFORMATION**

<b>Basis for Assessment</b>	: Information given is based on product testing, and/or similar products, and/or components.
<b>Acute Oral Toxicity</b>	: Expected to be of low toxicity: LD50 >2000 mg/kg , Rat Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
<b>Acute Dermal Toxicity</b>	: Expected to be of low toxicity: LD50 >2000 mg/kg , Rat
<b>Acute Inhalation Toxicity</b>	: Low toxicity: LC50 greater than near-saturated vapour concentration. / 1 hours, Rat
<b>Skin Irritation</b>	: May cause moderate skin irritation (but insufficient to classify). Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
<b>Eye Irritation</b>	: Essentially non-irritating to eyes.
<b>Respiratory Irritation</b>	: Inhalation of vapours or mists may cause irritation to the respiratory system. Insufficient to classify.
<b>Repeated Dose Toxicity</b>	: Kidney: caused kidney effects in male rats which are not considered relevant to humans
<b>Carcinogenicity</b>	: Repeated exposure causes skin tumour promotion in



experimental animals.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown. (Stoddard solvent IIC)  
Not classified as a carcinogen.

**Additional Information** : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

**12. ECOLOGICAL INFORMATION**

**Acute Toxicity**

- Fish** : Low toxicity: LC/EC/IC50 > 1000 mg/l
- Aquatic Invertebrates** : Low toxicity: LC/EC/IC50 > 1000 mg/l
- Algae** : Low toxicity: LC/EC/IC50 > 1000 mg/l
- Microorganisms** : Expected to be toxic: 1 < LC/EC/IC50 <= 10 mg/l

**Mobility** : Adsorbs to soil and has low mobility.  
Floats on water.

**Persistence/degradability** : Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

**Bioaccumulation** : Has the potential to bioaccumulate.

**Other Adverse Effects** :

**13. DISPOSAL CONSIDERATIONS**

**Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.

**Container Disposal** : Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

**Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

**14. TRANSPORT INFORMATION**

**US Department of Transportation Classification (49CFR)**

- Identification number UN 1268
- Proper shipping name Petroleum distillates, n.o.s.
- Class / Division 3
- Packing group III
- Contains OIL



Material Safety Data Sheet

Emergency Response Guide No. 128

Additional Information: This material is an 'OIL' under 49 CFR Part 130 when transported in a container of 3500 gallon capacity or greater.

IMDG

Identification number: UN 1268
Proper shipping name: PETROLEUM DISTILLATES, N.O.S.
Class / Division: 3
Packing group: III
Marine pollutant: No

IATA (Country variations may apply)

Identification number: UN 1268
Proper shipping name: Petroleum distillates, n.o.s.
Class / Division: 3
Packing group: III

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

AICS Listed.
DSL Listed.
INV (CN) Listed.
TSCA Listed.
EINECS Listed. 265-191-7
KECI (KR) Listed. KE-31664
PICCS (PH) Listed.

SARA Hazard Categories (311/312)

Fire Hazard. Delayed (Chronic) Health Hazard.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.





---

16. OTHER INFORMATION

**HMIS Rating (Health, Fire, Reactivity)** : 1, 2, 0

**NFPA Rating (Health, Fire, Reactivity)** : 1, 2, 0

**MSDS Version Number** : 9.

**MSDS Effective Date** : 04/11/2009

**MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.

**MSDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Uses and Restrictions** : Industrial Solvent.

**MSDS Distribution** : The information in this document should be made available to all who may handle the product

**Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.