



MATERIAL SAFETY DATA SHEET

PX-70

PARISER INDUSTRIES

TRADE SECRET REGISTRY #

307554-5303P

PRODUCT NAME: PX-70

TRADE SECRET REGISTRY #

HMIS CODES: H F R P

UN NUMBER : N/A

2 0 1 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PARISER INDUSTRIES
ADDRESS : 91 MICHIGAN AVE
PATERSON, NJ 07503

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 3/9/2006
INFORMATION PHONE : 973-569-9090 NAME OF PREPARER : ENVIRONMENTAL DEPT

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg	@ TEMP	PERCENT
ALKYLBENZENESULFONIC ACID PEL OF 2PPM (OSHA) TWA OF 2PPM (ACGIH)	MIXTURE	N/A	N/A	4.02
SODIUM HYDROXIDE, LIQUID OSHA-2MCM-8 HOUR TWA ACGIH-2MCM-CEILING	1310-73-2	1mmHG	N/A	
MONOETHANOLAMINE ACGIH: 3ppm OSHA: 3ppm PEL	141435	.2mm/mg	20øc	.90

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

pH 1% SOLUTION : 9.5 +/- .5
BOILING RANGE: 100°C - 339°F SPECIFIC GRAVITY (H2O=1): 1.12
VAPOR DENSITY: N/A EVAPORATION RATE: N/A
COATING V.O.C.: NOT APPLICABLE MATERIAL V.O.C.: NOT APPLICABLE
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: CLEAR AMBER LIQUID WITH SWEET ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : 280°F METHOD USED: SETA FLASH
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 6 UPPER: 17

EXTINGUISHING MEDIA:
FOR FIRES INVOLVING THIS PRODUCT, WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL MAY BE USED.

SPECIAL FIREFIGHTING PROCEDURES
WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS WHEN EITHER IN CONFINED AREAS OR EXPOSED TO COMBUSTION PRODUCTS.
USE WATER TO COOL FIRE EXPOSED CONTAINERS.



MATERIAL SAFETY DATA SHEET

PX-70

PARISER INDUSTRIES

TRADE SECRET REGISTRY #

307554-5303P

UNUSUAL FIRE AND EXPLOSION HAZARDS

NONE

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATION ALDEHYDES AND KEYTONES MAY BE FORMED ON BURNING. HEATING IN AIR MAY PRODUCE IRRITATING ALDEHYDES, ACIDS AND KEYTONES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE IRRITATION OF THE NOSE AND THROAT. HIGH CONCENTRATION MAY CAUSE COUGHING AND CHOKING.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITANT, REDDENING OF SKIN. SKIN DAMAGE. SEVERE IRRITATION TO EYES.

FLUSH EYES AND SKIN WITH PLENTY OF WATER FOR A LEAST 15 MINUTES. CALL A PHYSICIAN IF IRRITATION OCCURS

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SEE ABOVE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION CAN CAUSE BURNING PAIN IN THE MOUTH, THROAT AND ABDOMEN; SEVERE SWELLING OF THE LARYNX; SKELETAL MUSCLE

PARALYSIS AFFECTING THE ABILITY TO BREATHE; CIRCULATORY SHOCK; AND/OR CONVUSIONS. MAY BE FATAL.

HEALTH HAZARDS (ACUTE AND CHRONIC)

SEE ABOVE

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: IF PATIENT IS FULLY CONSCIOUS, GIVE 2 GLASSES OF WATER. INDUCE VOMITING. OBTAIN MEDICAL ATTENTION. SKIN:

REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. OBTAIN MEDICAL ATTENTION IF IRRITATION PERSISTS.

INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH WATER AND CONTINUE FLUSHING FOR 15 MINUTES. OBTAIN MEDICAL



MATERIAL SAFETY DATA SHEET

PX-70

PARISER INDUSTRIES

TRADE SECRET REGISTRY #

307554-5303P

ATTENTION WITHOUT DELAY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

CONTAIN SPILL IF POSSIBLE, WITH ABSORBENT MATERIALS SUCH AS CLAY OR SOIL AND SHOVEL UP. AVOID SKIN AND EYE CONTACT.

WASTE DISPOSAL METHOD

IF MATERIAL CAN NOT BE SALVAGED, A METHOD IS NEUTRALATION FOLLOWED BY DISCHARGE INTO A TREATMENT SYSTEM IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT HANDLE UNLESS THE SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. AVOID EYE AND SKIN CONTACT. AVOID INHALATION OF VAPORS. DO NOT PUNCTURE, DRAG OR SLIDE CONTAINERS. DO NOT SMOKE IN ANY CHEMICAL HANDLING OR STORAGE AREA. WASH HANDS BEFORE EATING. STORE IN A COOL, DRY AND WELL-VENTILATED LOCATION. PROTECT FROM HUMIDITY. KEEP CONTAINERS TIGHTLY CLOSED. STORE AWAY FROM INCOMPATIBLE MATERIALS.

OTHER PRECAUTIONS

USE WITH ADEQUATE VENTILATION OR LOCAL EXHAUST. STORE IN A COOL, DRY WELL VENTILATED AREA. KEEP CONTAINER CLOSED WHEN NOT IN USE.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

USE SELF-CONTAINED BREATHING APPARATUS IN HIGH VAPOR CONCENTRATIONS.

VENTILATION

GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF.

PROTECTIVE GLOVES

NORMAL WORK GLOVES ARE ADEQUATE.

EYE PROTECTION

WEAR CHEMICAL SAFETY GOGGLES PLUS FULL FACE SHIELD TO PROTECT AGAINST SPLASHING.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

EYE BATH, SAFETY SHOWER

WORK/HYGIENIC PRACTICES

WARM WATER SHOWERING, HANDWASHING AND EYEWASH STATIONS ARE RECOMMENDED IN THE WORK AREA. THOROUGHLY WASH WITH SOAP AND WATER BEFORE HANDLING FOOD, SMOKING OR APPLYING MAKEUP. WASH CONTAMINATED CLOTHING AND DRY BEFORE REUSE.

===== SECTION IX - DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY PARISER INDUSTRIES, INC., TO BE ACCURATE. AS WITH ALL CHEMICALS, KEEP AWAY FROM CHILDREN, ANIMALS, AND FOOD PRODUCTS. FOR



MATERIAL SAFETY DATA SHEET

PX-70

Page: 4
3/9/2006

PARISER INDUSTRIES

TRADE SECRET REGISTRY #

307554-5303P

INDUSTRIAL USE ONLY, USE AS DIRECTED.

===== SECTION X - UN CODE =====

N/A