

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 001

MSDS NO: 66465

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 11/11/05

VERSION: 002

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

NS FARRINGTON
2355 FARRINGTON POINT DR

WINSTN SALEM,NC 27107

UNIVAR USA INC.

(425)889-3400

6100 CARILLON POINT , KIRKLAND

, WA 98033

----- EMERGENCY ASSISTANCE -----

FOR EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC
(800)424-9300

PRODUCT NAME: VM&P NAPHTHA
MSDS NUMBER: 66465
DATE ISSUED: 8/15/2005
SUPERSEDES: 7/23/2003
ISSUED BY: 006341

MSDS Document
Product VM&P Naphtha

1. Chemical Product and Company Identification
Trade Name of this Product VM&P Naphtha

Distributed by:
Univar USA Inc.
6100 Carillon Point
Kirkland, WA 98003-7357
425-889-5000

Emergency Phone CHEMTREC (800) 424-9300
Revision Date 8/15/2005

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

Health 1
Fire 3
Reactivity 0
Specific

2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Light Aliphatic Solvent	64742-89-8	100 %	0		
Naptha					

3. Hazard Identification

*****EMERGENCY OVERVIEW*****

- * WARNING: Flammable Liquid and Vapor. The Flash Point is <100 degrees F. *
 - This product is a clear, water-white, light hydrocarbon liquid.
 - * It has a solvent petroleum odor. The product floats on water.
 - * When burned the product produces carbon monoxide and other asphyxiants during combustion.
 - * Harmful if inhaled and may cause delayed lung injury.
 - * Aspiration hazard if swallowed - can enter lungs and cause damage.
 - * Keep away from heat, sparks, and flame.
 - * Avoid breathing vapor. Use ventilation to keep vapor below exposure limits.
 - * Avoid contact with eyes, skin and clothing. Material splashed into the eyes will irritate tissues. Gently flush material from eyes with clean water.
 - * Unprotected exposure to this product will cause skin dryness.
 - * Remove product soaked clothing and wash with mild soap.
 - * As with any petroleum product, avoid mixing this product with strong oxidizers.
 - * This product is not listed on the NTP, IARC, OSHA, or ACGIH lists of suspected/confirmed carcinogens.
 - * This product may be toxic to fish but will be toxic to birds and wildlife through ingestion during pelage cleaning.
 - * This product is readily biodegradable in the presence of air and sunlight.
 - * Spilled material is slippery and may cause falls.
- *****END OF EMERGENCY OVERVIEW *****

POTENTIAL HEALTH EFFECTS
PRIMARY ROUTE(S) OF ENTRY
Skin.

EYES
Tests on similar materials suggest acute irritation be expected.

SKIN
Tests on similar materials indicate acute irritation is expected to occur upon short-term exposure, chronic dermatitis on prolonged contact.

INGESTION

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 003

MSDS NO: 66465

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 11/11/05

VERSION: 002

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

ACUTE ASPIRATION HAZARD. Tests on similar materials indicate possibility of the following symptoms: headache, nausea, drowsiness, fatigue, pneumonitis, pulmonary edema, central nervous system depression, convulsions, and loss of consciousness.

INHALATION

Tests on similar material indicate the possibility of the following symptoms: headache, nasal and respiratory irritation, nausea, drowsiness, breathlessness, fatigue, central nervous system depression, convulsions, and loss of consciousness.

CHRONIC (CANCER INFORMATION)

Prolonged and/or repeated contact with this material may produce skin irritation and inflammation.

Carcinogen listed by :

National Toxicology Program (No)

I. A. R. C. (NO)

OSHA (NO)

ACGIH (NO)

This product does not require a cancer hazard warning in accordance with the OSHA Hazard Communication Standard.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Personnel with pre-existing skin disorders should avoid contact with this product.

4. First Aid Information

EYES

Flush eyes immediately with water for at least 15 minutes or until irritation subsides, occasionally lifting lower and upper lids. Get medical attention promptly.

SKIN

Wash thoroughly with soap and water. Immediately remove contaminated clothing and wash before reuse. If irritation or rash develops, obtain medical assistance. Immediately remove soaked clothing.

INGESTION

CALL PHYSICIAN IMMEDIATELY. Do not induce vomiting except at the instruction of a physician. Never give anything by mouth to an unconscious person.

INHALATION

Remove patient to fresh air and consult a physician. If breathing is difficult, give oxygen. If not breathing give artificial respiration.

5. Fire Fighting Measures

FLAMMABLE PROPERTIES

FLASH POINT: >50 deg F >10 deg C Tag Closed Cup (D56)

AUTOIGNITION: 620 ave deg F 327 ave deg C

FLAMMABILITY CLASS: IB

LOWER EXPLOSIVE LIMIT (%): 1 vol % (estimated)

UPPER EXPLOSIVE LIMIT (%): 7 vol % (estimated)

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

FIRE AND EXPLOSION HAZARDS

Can form flammable mixtures with air and flash at room temperature or upon slight heat application. Vapors are heavier than air and may travel considerable distance. Explosion hazard in confined spaces if exposed to ignition source. Mists or sprays may be flammable below oil's normal flash point. Keep away from heat or open flame.

EXTINGUISHING MEDIA

Dry Chemical, carbon dioxide, and foam. NOTE: Water, fog and foam may cause frothing and spattering. Water stream may spread fire.

FIRE FIGHTING INSTRUCTIONS

Use water to cool containers exposed to flames. Do not enter enclosed or a confined work space without proper protective equipment. Fire fighting personnel should wear respiratory protection(positive pressure if available). If leak or spill has not ignited, use water spray to disperse the vapors.

Products of combustion include fumes, smoke and carbon monoxide.

6. Accidental Release Measures

Evacuate area and shut off ignition source. Contain spill and keep from entering waterways or sewers. Use personal protective equipment. Advise EPA; state agency if required. Absorb on inert material. Shovel, sweep or vacuum spill and place in closed container for disposal.

7. Handling and Storage

HANDLING: Keep product away from high energy ignition sources, heat, sparks, pilot lights, static electricity, and open flame. Avoid contact with skin. Avoid inhalation of vapors or mists. Use in well ventilated area away from all ignition sources. See Section 8 for additional personal protection advice when handling this product.

STORAGE: Store in a cool area.

SPECIAL PRECAUTIONS: To prevent and minimize fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system. Electrical equipment and fittings must comply with local fire prevention regulations for this class of product. Use the correct grounding procedures. Refer to national or local regulations covering safety at petroleum handling and storage areas for this product.

EMPTY CONTAINER WARNING: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.

8. Exposure Controls and Personal Protection

ENGINEERING CONTROLS

Use adequate ventilation to keep oil mists of this material below applicable standard(s). See Section on occupational exposure limits.

EYE/FACE PROTECTION

Safety glasses, splash goggles, or face shield as appropriate. Have suitable eye wash water available.

SKIN PROTECTION

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing. Acceptable materials for gloves are neoprene; nitrile; viton.

RESPIRATORY PROTECTION

Up to 1000 ppm, half mask organic vapor respirator. Up to 5000 ppm, full face organic vapor respirator or full face supplied air respirator. Greater than 5000 ppm, fire fighting, or unknown concentration, self contained breathing apparatus with positive pressure should be used.

OTHER/GENERAL PROTECTION

If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard).

Maintain local or dilution ventilation to keep air concentration below 100 ppm. Loading, unloading, tank gauging, etc., remain upwind. Request assistance of safety and industrial hygiene personnel to determine air concentrations.

INGREDIENT NAME, CAS #, EXPOSURE LIMITS, PERCENT BY VOLUME

Light Aliphatic Solvent Naphtha ,CAS NUMBER: 64742-89-8,TWA-300ppm, 100 Petroleum Distillate (Naphtha)

9. Physical and Chemical Properties

APPEARANCE Clear liquid.

ODOR Petroleum Naphtha.

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

ODOR THRESHOLD N.D.

BASIC PHYSICAL PROPERTIES PHYSICAL STATE: Liquid

BOILING POINT: IBP >242 deg F IBP >117 deg C

MELTING POINT: n/ay. deg F n/ay. deg C

VAPOR PRESSURE: 0.28371 psia @ 68 deg F

VAPOR DENSITY (AIR=1): n/av

SPECIFIC GRAVITY: 0.74 Water = 1

MOLECULAR WEIGHT: 118.00

SOLUBILITY (H2O): negligible in water

PERCENT VOLATILES: 100%

VISCOSITY: n/av

Physical data may vary slightly to meet specifications.

10. Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY) Sources of ignition.

INCOMPATIBLE MATERIALS Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

Incomplete combustion may produce fumes, smoke, carbon monoxide and other asphyxiants.

HAZARDOUS POLYMERIZATION: will not occur

11. Toxicological Information

Skin effects

May cause irritation or dermatitis with prolonged and repeated contact.

Oral effects

Tests on similar materials indicate an order of acute oral toxicity.

Inhalation effects

Acute toxicity expected on inhalation.

Medical conditions aggravated by overexposure

Dermatitis and sensitive skin - this product is not listed as carcinogenic or a potential carcinogen by the national toxicology program, by the I.A.R.C. monographs or by OSHA. Nevertheless, good industrial hygienic practices are recommended.

12. Ecological Information

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

This product is rapidly biodegradable. Biodegradation is possible within 90 to 120 days in aerobic environments at temperatures above 70o F (21o C).

13. Disposal Considerations

Product as supplied does not meet the characteristics of a hazardous waste

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 007

MSDS NO: 66465

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 11/11/05

VERSION: 002

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

as defined in 40 CFR 261.21-24. If mixed with other products, waste mixture must be characterized. DO NOT dispose of this product in drains or storm sewers. DO NOT dispose of this product in a landfill without prior solidification. Waste product should be recycled. Consider waste brokering.

14. Transportation Information

PROPER SHIPPING NAME: Petroleum Distillates, nos, Class 3, UN 1268, PG II

HAZARD CLASS: Class 3 Flammable Liquid

DOT IDENTIFICATION NUMBER: UN1268

DOT SHIPPING LABEL: DOT Hazardous Material

15. Regulatory Information

U.S. FEDERAL REGULATORY INFORMATION

SARA 302 Threshold Planning Quantity: NOT APPLICABLE

SARA 304 Reportable Quantity: NOT APPLICABLE

SARA TITLE III - Section 311/312 Hazard classes:

Immediate/Acute Health Effects: no

Delayed/Chronic Health Effects: no

Fire Hazard: yes

Sudden Release of Pressure Hazard: no

Reactivity Hazard: no

EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory of chemicals.

SARA TITLE III - Section 313 Supplier notification:

The following chemicals are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and reauthorization Act of 1986 and 40 CFR Part 372:

Ethylbenzene CAS # 100-41-4 Up to 1 wt %

Cumene CAS # 98-82-8 Up to 1 wt %

Toluene CAS # 108-88-3 Up to 1 wt %

Xylene CAS # 1330-20-7 Up to 6 wt %

1,2,4-Trimethylbenzene CAS # 95-63-6 Up to 1 wt %

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): No chemicals in this product are subject to the reporting requirements of CERCLA Section 101(14)(F). When this product is used in a mixture, or as an ingredient in another product, or in a manufacturing operation, the petroleum exclusion may terminate and an accidental spill may require reporting to the National Response Center.

California Proposition 65

This material may contain the following components which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 008

MSDS NO: 66465

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 11/11/05

VERSION: 002

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

Ethylbenzene CAS # 100-41-4 Up to 1 wt %

Toluene CAS # 108-88-3 Up to 1 wt

Cumene CAS # 98-82-8 Up to 1 wt %

1,2,4-Trimethylbenzene CAS # 95-63-6 Up to 1 wt %

CANADIAN REGULATORY INFORMATION

The components of this product are listed on the Canadian (DSL) Domestic Substances List.

EUROPEAN (ECC) REGULATORY INFORMATION

The components of this product are listed on the European Inventory of Existing Commercial Substances. EINECS# 265-192-2

16. Other Information

DATE REVISED: 8/15/05 SECTION NO. updated section 15

----- FOR ADDITIONAL INFORMATION -----

CONTACT: MSDS COORDINATOR

UNIVAR USA INC.

DURING BUSINESS HOURS, PACIFIC TIME

(425)889-3400

01/12/06 10:01

PRODUCT: 695184

CUST NO: 188978

ORDER NO: 339912

----- NOTICE -----

***** UNIVAR USA INC("UNIVAR"), EXPRESSLY DISCLAIMS

ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED

HEREIN, AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR

CONSEQUENTIAL DAMAGES. **

DO NOT USE INGREDIENT INFORMATION AND/OR PERCENTAGES IN THIS MSDS AS A
PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT
SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM
YOUR LOCAL UNIVAR SALES OFFICE.

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 009

MSDS NO: 66465

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 11/11/05

VERSION: 002

PRODUCT: VM&P NAPHTHA

ORDER NO: 339912

PROD NO : 695184

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVARS CONTROL AND THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM THE PUBLICATION OR USE OF, OR RELIANCE UPON , INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER PROCESS.

* * * E N D O F M S D S * * *