

## MATERIAL SAFETY DATA SHEET

FABRITEC INTERNATIONAL  
 1157 INDUSTRIAL ROAD  
 COLD SPRING, KY 41076  
 EMERGENCY CONTACT: HAROLD E. MAINS (859) 781-8200  
 CHEMTREC ASSISTANCE: (800) 424-9300 (U.S.A. & CANADA)

MSDS NO.: 6748  
 DATE: OCT. 2007  
 PAGE: 1 OF 2

## 1. PRODUCT NAME &amp; HAZARD SUMMARY

**6748 VOL** VOLATILE SPOTTER  
 PRIMARY USE: SPOT REMOVAL

NFPA HAZARD	RATING	SARA TITLE III, SECTION 313	CANADA (WHMIS)
HEALTH	2 MODERATE	APPLICABLE ( )	B: FLAMMABLE, COMBUSTIBLE
FIRE	1 SLIGHT	NOT APPLICABLE (X)	D2: CAUSING OTHER TOXIC EFFECTS
REACTIVITY	0 MINIMAL		

## 2. HAZARDOUS COMPONENTS

	%	OSHA (PPM)	ACGIH (PPM)	LD 50 (MG/KG)	
Synthetic isoparaffinic hydrocarbons C.A.S. #64741-66-8	40-70	PEL N/Av	TWA 400	STEL >5000 rat. oral	N.AV.
Halogenated hydrocarbon C.A.S. Trade Secret	30-60	200	200	5000	N.AV.
Glycol ether C.A.S. :Trade Secret	2-5	N/Av	20	3000	N.AV.

INGREDIENTS NOT IDENTIFIED ARE NON-HAZARDOUS.

## 3. PHYSICAL &amp; CHEMICAL DATA

APPEARANCE: CLEAR, WATER WHITE LIQUID	EVAPORATION RATE (n-BuOAC = 1): 3.0 (ESTIMATE)
ODOR: ETHER-LIKE	VAPOR DENSITY (AIR =1): N.AV.
BOILING PT.: 90-350°F (32-176°C)	VAPOR PRESSURE (MM): 140mm (68°F)
FREEZING PT.: <20°C	SOLUBILITY IN WATER: 20%
pH: N.AP.	SPECIFIC GRAVITY (WATER = 1): 0.898
% VOLATILE: 100%	CO-EFFICIENT OF WATER/OIL DISTRIBUTION: N.AV.
ODOR THRESHOLD (PPM): N.AV.	

## 4. FIRE &amp; EXPLOSION HAZARDS

FLASH POINT: >141°F (61°C)  
 FLAMMABLE LIMITS IN AIR, % BY VOLUME: Not determined  
 FIRE FIGHTING MEDIA (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5): Dry chemical, CO<sub>2</sub>, water spray or alcohol foam.  
 SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus.  
 UNUSUAL FIRE AND EXPLOSION: None  
 HAZARDOUS COMBUSTION PRODUCTS: Hydrogen Chloride Gas, Hydrogen Fluoride, Oxides of Carbon.  
 CONDITIONS OF FLAMMABILITY: N.AV.  
 AUTO IGNITION TEMP. (°C): N.AV.  
 EXPLOSION DATA: - SENSITIVITY TO MECHANICAL IMPACT: N.AP.  
 SENSITIVITY TO STATIC DISCHARGE: N.AV.

## 5. REACTIVITY HAZARD DATA

STABILITY (CONDITIONS TO AVOID): Stable  
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, caustic material, and acids. Avoid contact with Aluminum.  
 HAZARDOUS DECOMPOSITION PRODUCTS: Extreme thermal decomposition may release Hydrogen Chloride Gas, Hydrogen Fluoride Gas.  
 HAZARDOUS POLYMERIZATION (CONDITIONS TO AVOID): Will not occur

## 6. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY:            INHALATION\_\_X\_\_ SKIN\_\_X\_\_            INGESTION\_\_\_\_\_

WARNING! MAY CAUSE EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED.  
SIGNS & SYMPTOMS OF EXPOSURE: (ACUTE & CHRONIC)

EYES: Liquid and vapors may cause irritation.  
 SKIN: May cause irritation and defatting of skin, which can lead to irritation, dermatitis.  
 INGESTION: of a large dose may cause abdominal pain, nausea and vomiting. May produce central nervous system depression with drowsiness, headache, dizziness, loss of coordination.

## 6. HEALTH HAZARD DATA (cont'd)

INHALATION: May cause irritation of throat, dizziness, headache, nausea and vomiting. May cause central nervous system depression.

IRRITANCY OF PRODUCT: N.AV.

SENSITIZATION TO PRODUCT: N.AV.

CARCINOGENICITY, REPRODUCTIVE TOXICITY, TERATOGENICITY, MUTAGENICITY: N.AV.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: N.AV.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Remove contact lenses, if worn. Flush with water for at least 15 min. Call a physician.

SKIN: Remove contaminated clothing, wash affected area with soap and water. If any symptoms of contact appear, get medical help.

INHALATION: Remove to fresh air. If breathing has stopped, perform artificial respiration. Keep person warm and at rest. Get medical attention immediately.

INGESTION: Treat symptomatically and supportively. Get medical attention immediately. If vomiting occurs, keep head lower than hips to prevent aspiration into lungs.

## 7. SPILL AND LEAK PROCEDURES

LARGE SPILLS: Contain and transfer to drums for use or disposal.

SMALL SPILLS: Absorb onto rags. Clean rags in cleaning unit.

WASTE DISPOSAL METHOD: May be considered a hazardous waste, dispose of according to all applicable regulations. Incineration in permitted facilities or disposal in permitted land fill are preferred disposal methods.

HANDLING PROCEDURES & EQUIPMENT: Avoid direct contact, wear respirator if vapors are present.

STORAGE REQUIREMENTS: Keep away from high heat areas.

## 8. SPECIAL PROTECTION, PREVENTATIVE MEASURES/IN CASE OF LARGE SPILL OR FIRE

ENGINEERING CONTROLS/VENTILATION: Local exhaust system sufficient to maintain exposure below TWA values

RESPIRATOR: THE FOLLOWING RESPIRATORS ARE RECOMMENDED & RANKED IN ORDER FROM MIN. TO MAX. PROTECTION:

CHEMICAL CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE WITH A FULL FACE PIECE.

GAS MASK WITH ORGANIC VAPOR CANISTER WITH A FULL FACE PIECE.

TYPE "C" SUPPLIED-AIR RESPIRATOR WITH FULL FACE PIECE.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND.

PERSONAL PROTECTIVE EQUIPMENT: Wear goggles when handling product, petroleum solvent resistant gloves.

## 9. TRANSPORTATION DATA

DOT HAZARD CLASSIFICATION 49 CFR 172.101: Combustible liquid, not regulated.

DOT LABEL: None

U.N./IATA: Not regulated

## 10. STATE RIGHT TO KNOW INFORMATION

SYNTHETIC ISOPARAFFINIC HYDROCARBONS C.A.S. #64741-66-8, HALOGENATED HYDROCARBON C.A.S. # TRADE SECRET, GLYCOL ETHER, C.A.S. # TRADE SECRET

## ABBREVIATIONS:

OSHA = Occupational Safety & Health Administration

TWA = Time Weighted Average for 8 Hours

Mg/M<sup>3</sup> = Milligrams per Cubic Meter of Air

NFPA = National Fire Protection Agency

(C) = Ceiling, Limit for Exposure

DOT = Department of Transportation

MG/KG = Milligrams per Kilogram (1,000 grams)

WHMIS = Workplace Hazardous Materials Information System - Canada

ACGIH = American Conference of Government Industrial Hygienists

R.Q. = Amount of spill that must be reported to EPA

SARA Title III, Sec. 313 = Superfund Amendments and Reauthorization Act

C.A.S. = Chemical Abstract Service Number

LD 50 = Lethal Dose for 50% Test Animals

PEL = Permissible Exposure Level

STEL = Short Term Exposure Level (15 min)

ppm = part(s) per million

SKN = Skin Effects

IATA = International Air Transport Association

N.AV. = Not Available

N.AP. = Not Applicable

U.N. = United Nations

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS, MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS. WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM THE HANDLING AND USE OF OUR PRODUCTS, WHETHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS.